

PT-VMZ501K

The World's Smallest and Lightest 5,000lm LCD Laser Projector



5,000lm	WUXGA	3,000,000:1
---------	-------	-------------

Item	Description	
패널	0.64" (16:10 비율) LCD × 3	
해상도	WUXGA (1920x1200) ,4K,30p 입력지원	
광 원	Laser diodes (20,000H)	
밝 기	5,000 ANSI lm	
명암비	3,000,000:1 (Dynamic Mode/ Dynamic Contrast 1)	
주변조도비	85%	
스크린 사이즈	0.76~7.62 m (30~300 in) 16:10 aspect ratio	
렌즈	1.6x Manual zoom (Throw Ratio 1.09 - 1.77 :1), F = 1.60 - 2.12, f = 15.30 - 24.64 mm	
터미널	HDMI IN	HDMI 19-pin × 2 (Compatible with HDCP, Deep Color, 4K/30p signal input)
	RGB 1 IN	D-sub HD 15-pin (female) x 1 (RGB/YPB PR/YCBCR)
	RGB 2 IN/MONITOR OUT	D-sub HD 15-pin (female) x 1 (RGB/YPB PR/YCBCR) [input/output switching]
	VIDEO IN	Pin jack x 1
	AUDIO 1/2 IN	M3 stereo mini jack x 2
	AUDIO 3 IN	Pin jack [L/R] x 1
	AUDIO OUT	M3 stereo mini jack x 1
	SERIAL IN	D-sub 9-pin x 1 for computer control (RS-232C compliant)
	LAN	RJ-45 x 1 for network control, 10Base-T, 100Base-TX, compatible with PLink™(Class 2)
	LAN/DIGITAL LINK	RJ-45 x 1 for network and DIGITAL LINK connection, HDBase-T™ compliant, 100Base-TX, compatible with PLink™(Class 2), HDCP, Deep Color , 4K/30p signal input
	USB CONNECTOR	USB (Type A) x 1 for Memory Viewer function, power supply [DC 5V, maximum 2A], Optional wireless module AJ-WM50 [TBD]
키스톤 보정	수직: ±25°, 수평: ±35°, 코너 보정 기능, 곡면 보정 기능	
렌즈쉬프트	수직: 0~-44 % (Manual) 수평: ±20% (Manual)	
스피커	Built -in 10W	
소음	37 dB (Normal Mode), 27 dB (Quiet Mode)	
전원	100~240 V AC, 50/60 Hz	
소비전력	370W	
크기(W×H×D)	399 x 115 x 348 mm (Not including protruding parts)	
무게	약 7.2kg	
기타 부가 기능	셔터(shutter)기능 ,Wireless Projection(Optional),Memory Viewer	